

FOX STRETCH WRAPPERS

FPS300 SEMI-AUTOMATIC LOW PROFILE

Production speed 1-40 LPH
Load size 55" W x 55" L x 90" H (78" Diagonal)
Weight capacity 5000 lbs.
PLC full color touch screen
Separate Top/Bottom wrap selectors 1-9
Film delivery system - Hurricane Thread
20" prestretch 210% factory set stretch
(50-250% available on request)



FPS400H SEMI-AUTOMATIC HIGH PROFILE

Production speed 1-40 LPH
Load size 55" W x 55" L x 82" H (80" Diagonal)
Weight capacity 5000 lbs.
PLC full color touch screen
Separate Top/Bottom wrap selectors 1-9
Film delivery system - Hurricane Thread
20" prestretch 210% factory set stretch
4 Heavy duty swivel table casters

THE HURRICANE THREAD CARRIAGE

(on all machines)

**THE HURRICANE THREAD HAS A BUILT IN
PATENTED END OF CYCLE FILM CUTTER AT NO EXTRA COST.**

A UNIQUE TOTAL MECHANICAL DEVICE THAT WORKS EVERYTIME AND BUILT TO LAST WHICH ELIMINATES THE NEED FOR KNIVES PLUS IT'S ONE LESS FUNCTION THE OPERATOR IS REQUIRED TO PERFORM

- HURRICANE THREAD® 20" prestretch film delivery system
- 210% factory set film stretch (50%-250% available upon request)
- **Easy thread film carriage**
- Electronic film force control on panel
- Adjustable mechanical force to load
- **Linear analog proximity sensor film feed speed control**
- 3/4HP AC MOTOR & DELTA 1 HP VFD variable speed film drive
- **Triple beam auto height eye capable of recognizing all colors including black**

